

# ► Technical Specifications

## Polycom® HDX EagleEye View™ Camera

### HDX Series Compatibility

- HDX 6000, HDX 7000, HDX 8000 and HDX 9000 Series

### Camera Specifications

- 10M Pixel CMOS Imager
- 4x Digital Zoom
- 55 Deg. HFOV at Min. Zoom
- Manual Pan range of +/- 45 deg
- Manual Tilt range of +5/-15 deg
- Output formats: SMPTE 296M 1280 x 720p, 50, 60 fps, SMPTE 274M 1920 x 1080P, 30/25 fps



### Audio

- Built-in Stereo Microphone arrays for room audio pickup. \* When used with EagleEye View 3M or 10M HDCI cables.

### Electrical

- Typical operating voltage/power: 12V @ < 1A

*These numbers were empirically collected under TYPICAL operating conditions. No attempt was made to force max power consumption. Voltages and currents are RMS. Power units are Volt-Amp.*

### Environmental Specification

- Operating Temperature: 0-40°C

### Physical Characteristics

- 1.99"(277mm)L x 3.9"(99mm)W x 4.2"(107mm)H
- 1.1 lbs

### Warranty

- One-year return to factory parts and labor

### Technical Documentation

- Documentation for setting up and using the HDX EagleEye View
- Visit: [www.polycom.com/vidodocumentation](http://www.polycom.com/vidodocumentation)

### Alternative Camera Views

